

14KW / 22KW / 44KW Twin Wallbox Series

Innovativeness


One charger with two output sockets
Business use with intelligent App control
Vandal resistant and anti-corrosion

Intelligent Control

Ethernet/4G/Wi-Fi communication all supported
OCPP communication protocol with CMS
Intelligent operation by App and cashless payment

Flexible Option

App operation or RFID authentication or plug and play
Customization with different color painting



Credit card payments
(Optional)





Model	YL14K-T1	YL22K-T2	YL44K-T3
Technical features			
Charging capacity	Up to 14KW(7KW*2)	Up to 22KW(11KW*2)	Up to 44KW(22KW*2)
Input/Output power	230VAC±20%-50/60Hz-32A*2-1phase	400VAC±20%-50/60Hz-16A*2-3phase	400VAC±20%-50/60Hz-32A*2-3phase
RCD	RCMU(Type A+ DC 6mA)/ Type B RCCB(Optional).		
Standby power	<5W		
Measuring accuracy	1%		
Energy Meter	MID certified		
OCPP	OCPP1.6 Json(OCPP2.0 optional)		
Communication	WIFI/Ethernet/4G(Optional)		
User interface	LCD 5 inch Touch Screen/ RFID(mifare iso& IEC 14443A)		
Certificate/Compliance	CE/FCC/ROHS/REACH/IEC/EN 61851-1 , IEC/EN61851-21-2, IEC/EN 62955, EN300328, EN 301489-1/-17,EN62479.		
Charging Interface	Type 2 socket*2 or Type 2 Gun *2 5M		
Special Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
Physical properties			
Warranty	2 years		
Protection	IP65, IK10,		
Enclosure	Galvanized steel		
Front Panel	Temper glass		
Installation	Wall-mount/Pole-mount.		
Cooling	Natural cooling		
Operating temperature	-30°C to +55°C		
Humidity	Max.95%(non-regulating)		
Product Dimensions	503*334*155(L*W*H)mm		
Package Dimension	610*415*250(L*W*H)mm		
Net Weight	13.5Kg	13.5Kg	13.5Kg
Gross Weight	15Kg	15Kg	15Kg